



| DOOR HEIGHT (m) | HEADROOM (DIM X) | INSIDE PROJECTION MOTOR (DIM Y) | INSIDE PROJECTION BARREL (DIM Z) |
|-----------------|------------------|---------------------------------|----------------------------------|
| 0 - 1.25 | 420mm | 360mm | 360mm |
| 1.25 - 2.0 | 430mm | 370mm | 370mm |
| 2.0 - 3.0 | 450mm | 385mm | 385mm |
| 3.0 - 4.0 | 450mm | 400mm | 400mm |
| 4.0 - 4.5 | 450mm | 430mm | 430mm |

PLEASE NOTE THE UP/DOWN BUTTONS AND SINGLE PHASE PLUG ARE INTENDED FOR SITE COMMISSIONING OF DOOR ONLY. IF RETAINED AS SURFACE MOUNTED, ANY CABLING UNDER 2m FROM FFL MUST BE PROTECTED. PUSH BUTTONS CAN BE REMOVED FROM ENCLOSURE AND FLUSH MOUNTED INTO WALL OR REPLACED WITH A KEY SWITCH (KEY SWITCH NOT INCLUDED).

We reserve the right to alter specification without notice and without incurring obligation

STEEL ROLLER SHUTTER – STANDARD GUIDES
INTERNAL BARREL MOTORISING – GENERAL ARRANGEMENT



| | | | | | | | | |
|------|----------|----|-------------------|----------|--------|----|-------------|------|
| C | 13.12.13 | TS | MATERIAL – FINISH | CODE No. | SCALE | : | DRG No. | ISS. |
| B | 28.05.13 | TS | | | DRAWN | TS | 24.04.13 | |
| ISS. | DATE | BY | | | APPVD. | | SRS_STD_IBM | C |